



## WA500 HEAVY DUTY WALLPAPER ADHESIVE

### 1 – DESCRIPTION

**Akfix WA500** is a premium Wallpaper Adhesive which is based on cold water dispersible starch derivative.

### 2 – PROPERTIES

- Easy to apply.
- Thanks to quick dissolving adhesive, viscosity rise quickly.
- Allows time for positioning.
- Makes future removal quick and easy.
- Dissolves in water with ease.
- Can be cleaned with a sponge and water.
- Contains anti-fungal & bacterial protection.

### 3 - APPLICATIONS

Thoroughly clean walls and ceilings. Painted walls and highly glazed non-porous walls should be lightly sanded and washed down. Old wall coverings and paste must be removed with a Wallpaper Remover. Porous substrates should be sized. Allow thoroughly drying before hanging wallpapers / wall coverings.

### 4 - INSTRUCTIONS

Add the adhesive slowly, in preferably warm, water in accordance with the figures shown below. Stir the mixture and allow the adhesive dissolve in the water. Make sure that substrates are clean, dry and smooth. Roll the mixture to the back of wallpapers.

### 5- PACKAGING

<i>Product</i>	<i>Weight</i>	<i>Package</i>
<b>WA500</b>	250 gr	50
<b>WA500</b>	25 kg	1

### 6- STORAGE AND SHELF LIFE

24 months in unopened cartridge if stored under dry and cool conditions

### 7- SAFETY

- Must be used in well ventilated areas.
- Must be kept away from children.
- The product contains preservative.



## 8- TECHNICAL PROPERTIES

<b>Basis</b>	: Carboxymethylated
<b>Appearance</b>	: Flakes
<b>Colour</b>	: White to creamy
<b>Viscosity at 3 min.</b>	: 8000 cPs at 23°C (Brookfield RTV, 20 rpm, Sp.3)
<b>pH</b>	: 8
<b>Temperature Resistance</b>	: -20°C to +70 °C
<b>Application Temperature</b>	: +5 °C to +35 °C

### Application Ratios

#### For 250gr s of adhesive

Paper Type	Amount of Water	Roll	Surface
Light paper	8,5 Liter	9-10	45-50 m <sup>2</sup>
Normal paper	6 Liter	9-7	38-45 m <sup>2</sup>
Heavy paper	4 Liter	5-6	25-30 m <sup>2</sup>